

Appl. No. 10/604,599
Amdt. dated January 05, 2006
Reply to Office action of 12/06/2005

Amendments TO the Claims:

The listing of claims will replace all prior versions, and listings, of claims in the application:

5 **Listing of Claims:**

Claims 1 – 20 (cancelled)

21. (Currently Amended) A color conversion apparatus for converting an input color
being in a first color space to an output color being in a second color space, wherein
10 both the input color and the output color include a plurality of color elements, the
apparatus comprising:

a first lookup table being coupled to a first color element of the input color for
outputting a corresponding first converted color element;

15 a second lookup table being coupled to a second color element of the input color for
outputting a corresponding second converted color element; and

20 an adder circuit being coupled to the first lookup table and the second lookup table
for summing the first converted color element and the second converted color
element to thereby generate a color element of the output color[.];
wherein both of the input color and the output color are in a RGB format including
R, G, and B components respectively representing red, green, and blue colors.

25 22. (Previously Presented) The apparatus of claim 21, further comprising:

a gamma correction circuit being coupled to a third color element of the input color
for generating a gamma corrected color element;

Appl. No. 10/604,599
Amdt. dated January 05, 2006
Reply to Office action of 12/06/2005

wherein the adder circuit is further coupled to the gamma correction circuit for summing the first converted color element, the second converted color element, and the gamma corrected color element to thereby generate the color element of the output color being in the second color space.

23. (Previously Presented) The apparatus of claim 21, wherein the adder circuit is further coupled to a third color element of the input color and is for summing the first converted color element, the second converted color element, and the third color element of the input color to thereby generate a temporary color element.

24. (Previously Presented) The apparatus of claim 23, further comprising a gamma correction circuit being coupled to the adder circuit for performing a gamma correction operation on the temporary color element outputted by the adder to thereby generate the color element of the output color being in the second color space.

25. (Previously Presented) The apparatus of claim 21, wherein the first lookup table maps a plurality of values for the first color element of the input color to a single corresponding value of the first converted color element, and the second lookup table maps a plurality of values for the second color element of the input color to a single corresponding value of the second converted color element.

26. (Previously Presented) The apparatus of claim 25, wherein within the first lookup table, eight values of the first color element of the input color map to a single corresponding value of the first converted color element; and within the second lookup table, eight values of the second color element of the input color map to a signal corresponding value of the second converted color element.

Appl. No. 10/604,599
Amdt. dated January 05, 2006
Reply to Office action of 12/06/2005

27. (Previously Presented) The apparatus of claim 21, wherein the first lookup table is indexed by using a number of bits from values of the first color element of the input color; and the second lookup table is indexed by using the number of bits from values of the second color element of the input color.
28. (Previously Presented) The apparatus of claim 27, wherein the number of bits comprise a number of most significant bits.
29. (Previously Presented) The apparatus of claim 21, wherein both the first lookup table and the second lookup table comprise a plurality of sub-tables for storing a relationship between the first color space and the second color space.
30. (Previously Presented) The apparatus of claim 21, wherein the apparatus is utilized in a liquid crystal display (LCD).
31. (Currently Amended) A method for converting an input color being in a first color space to an output color being in a second color space, wherein both the input color and the output color include a plurality of color elements, the method comprising:
- looking up a first color element of the input color in a first lookup table to determine a corresponding first converted color element;
- looking up a second color element of the input color in a second lookup table to determine a corresponding second converted color element; and
- summing the first converted color element and the second converted color element to thereby generate a color element of the output color[.];

Appl. No. 10/604,599
Amdt. dated January 05, 2006
Reply to Office action of 12/06/2005

wherein both of the input color and the output color are in a RGB format including
R, G, and B components respectively representing red, green, and blue colors.

32. (Previously Presented) The method of claim 31, further comprising:

5

generating a gamma corrected color element according to a third color element of
the input color; and

10

summing the first converted color element, the second converted color element, and
the gamma corrected color element to thereby generate the color element of the
output color being in the second color space.

33. (Previously Presented) The method of claim 31, further comprising summing the
first converted color element, the second converted color element, and a third color
15 element of the input color to thereby generate a temporary color element.

34. (Previously Presented) The method of claim 33, further comprising performing a
gamma correction operation on the temporary color element of the output color to
thereby generate the color element of the output color being in the second color
20 space.

35. (Previously Presented) The method of claim 31, wherein the first lookup table
maps a plurality of values for the first color element of the input color to a single
corresponding value of the first converted color element, and the second lookup
25 table maps a plurality of values for the second color element of the input color to a
single corresponding value of the second converted color element.

36. (Previously Presented) The method of claim 35, wherein within the first lookup

Appl. No. 10/604,599
Amdt. dated January 05, 2006
Reply to Office action of 12/06/2005

table, eight values of the first color element of the input color map to a single corresponding value of the first converted color element; and within the second lookup table, eight values of the second color element of the input color map to a signal corresponding value of the second converted color element.

5

37. (Previously Presented) The method of claim 31, further comprising:

indexing the first lookup table by a number of bits from values of the first color element of the input color; and

10

indexing the second lookup table by the number of bits from values of the second color element of the input color.

15

38. (Previously Presented) The method of claim 37, wherein the number of bits comprise a number of most significant bits.

20

39. (Previously Presented) The method of claim 31, further comprising storing a relationship between the first color space and the second color space within a plurality of sub-tables in both the first lookup table and the second lookup table.

40. (Previously Presented) The method of claim 31, wherein the method is utilized in a liquid crystal display (LCD).